



Expanding Wired Connectivity for Home/Office Networks

The NETGEAR 200 Series Unmanaged Switches provide easy and affordable network connectivity to home and small offices. They are easy to use and reliable. With these plug-and-play switches, you can expand your network connections to multiple devices instantly. The 200 Series also supports the efficient use of energy, helping you save power and money.


- Fast Ethernet or Gigabit Ethernet connectivity
- Auto-MDI/MDIX eliminates the need for crossover cables
- Energy-efficient technology for power savings
- Auto-negotiation for automatic connection at the highest common speed between switch and an end device
- Non-blocking switching architecture for maximum throughput at wire speed

Ideal for Home Networks

- Plug-and-play
- Fanless for silent operation
- Compact design
- LED indicators for ease of use

Ideal for
**HOME
NETWORKS**

HOME/OFFICE NETWORK DIAGRAM



FEATURES	FS205	FS208	GS205	GS208
10/100Mbps PORTS	5	8		
10/100/1000Mbps PORTS			5	8
ENCLOSURE	Plastic	Plastic	Plastic	Plastic
CONNECTOR TYPE	Plastic	Plastic	Plastic	Plastic
PERFORMANCE: Bandwidth Buffer Memory Jumbo Frames	1Gbps 384Kbits 2048 bytes	1.6Gbps 768Kbits 2048 bytes	10Gbps 1Mbit 9216 bytes	16Gbps 1Mbit 9216 bytes
ENERGY EFFICIENCY: Energy Efficient Ethernet (IEEE 802.3az) Auto Power Down Short Cable Detection DC Input Power Consumption (Max and Standby) Power On/Off Switch Heat Dissipation (Max and Standby)	● ● 5V/0.7A 1.8W/0.7W 6.14 BTU/2.39 BTU	● ● 5V/0.7A 2.3W/1.2W 7.85 BTU/4.10 BTU	● ● ● 5V/0.7A 2.34W/0.45W 7.99 BTU/1.53 BTU	● ● ● 12V/0.5A 3.52W/0.57W ● 12.01 BTU/1.95 BTU
PORT LED	Power, Link/Activity	Power, Link/Activity	Power, Link/Activity	Power, Link/Activity
ADDRESS TABLE SIZE	2K	2K	2K	8K
PHYSICAL SPECIFICATIONS: Width x Depth x Height Weight	110 x 71 x 26 mm 0.09 kg	152 x 93 x 26 mm 0.16 kg	110 x 71 x 23 mm 0.1 kg	152 x 92 x 26 mm 0.19 kg
ENVIRONMENT: Operating Temperature Storage Temperature Operating Humidity Storage Humidity	0 ~ 40°C -20 ~ 70°C 90% maximum relative humidity, non-condensing 5% to 95% relative humidity			

STANDARDS

- 802.3ab 1000BASE-T Gigabit Ethernet**
- 802.3u 100BASE-TX Fast Ethernet
- 802.3i 10BASE-T Ethernet IEEE
- 802.3az Energy Efficient Ethernet
- 802.3x Flow Control
- 802.3 CSMA/CD
- 802.1P QoS**

WARRANTY*

- All except EMEA: 1-year warranty
- EMEA: 2-year warranty



FS205



FS208



GS205



GS208

Actual SKU availability may vary per region. Please check the local website for product availability.

* This product comes with a limited warranty that is valid only if purchased from a NETGEAR authorized reseller, and modifications to product may void the warranty; see <http://www.netgear.com/about/warranty/> for details. 24/7 basic technical support provided for 90 days from purchase date when purchased from a NETGEAR authorized reseller.

** Applies to models GS205 and GS208 only.

† NETGEAR #1 in US Market Share according to NPD data for Unmanaged and Web/Smart Switches, April 2015.

NETGEAR, the NETGEAR logo are trademarks and/or registered trademarks of NETGEAR, Inc. and/or its subsidiaries in the United States and/or other countries. Other brand names mentioned herein are for identification purposes only and may be trademarks of their respective holder(s). Information is subject to change without notice.

© 2015 NETGEAR, Inc. All rights reserved.

NETGEAR, Inc. 350 E. Plumeria Drive, San Jose, CA 95134-1911 USA, 1-888-NETGEAR (638-4327), E-mail: info@NETGEAR.com, www.NETGEAR.com

D-200 Series-2

NETGEAR®

REPRESENTADO EN MÉXICO POR TELSMA MAYORISTA

Oriente 65A No. 2848, Asturias, Cuauhtémoc, 06850, CDMX, México

Tels.: +52 (55) 5740 2142 / 5740 0606 • ventas@telsa.com.mx • www.telsa.com.mx

Síguenos en: [Twitter.com/TelsaMayorista](https://twitter.com/TelsaMayorista) • [Facebook.com/TelsaMexico](https://facebook.com/TelsaMexico)



Contáctanos:

