



HSM-44-UHD

4K 4x4 Matrix Switch



FEATURES

- HDMI 2.0 version (Support 4K@60Hz YUV4:4:4)
- Bandwidth up to 18Gbps
- HDCP2.2 input ,HDCP2.2 output
- HDCP1.4 input, HDCP1.4 output
- Support HDR10
- 4xHDMI Input, 4xHDMI output
- Analog and Digital Audio extraction
- Any one of the 4 Ultra HD sources to any one of the 4 Ultra HD displays
- Support Panel Button, Local IR, RS232 Control with command, IP Control, Web GUI Control
- Support Dolby True HD and DTS-HD master audio, Dolby Atmos under copy EDID mode
- Support firmware updating through USB port

DESCRIPTION

As a member of Genesis Digital Matrix series of switchers, the HSM-44-UHD matrix provides exceptional quality, intuitive operation and powerful control methods that are hallmarks of Hall Technologies video matrix switchers. The 4K matrix is a 4x4 cross-point switch in a compact 1-RU enclosure.

The HSM-44-UHD supports HDMI resolutions up to 4K @ 60Hz4:4:4. It also supports HDCP 2.2 and 1.4, 3D, deep-color and PCM, Dolby, DTS, and HD audio standards. The matrix intelligently calculates EDID for each input based on the EDID of the connected sinks.

Users can save and recall multiple matrix routing configuration PRESETs. HDMI outputs can also be blanked. The matrix includes a two-line character LCD on it's front panel to display the current video routing and to facilitate creating or recalling presets.

The HSM-44-UHD matrix is ideal for conference rooms, multimedia presentations, digital signage, houses of worship, and many other settings.



Video Input Ports:	(4) HDMI 2.0
Video Output Ports:	(4) HDMI 2.0
HDCP:	HDCP 2.2 and HDCP 1.4
HDMI Bandwidth:	18 Gbps
HD Resolutions:	Up to 4K60 (4:4:4)
PC Resolutions:	VGA through WQXGA
Audio Output Ports:	(4) TOSLINK (S/PDIF digital supports all formats listed below) (4) 3.5 mm (Analog Stereo, L/R, supports only 2-channel formats) PCM 2.0, PCM 5.1, PCM 7.1, Dolby 5.1, DTS 5.1, DD+, D-TrueHD, DTS-HD 16/20/24 bits per sample and up to 96 KHz Sampling Rate
Control:	Front Panel / Telnet / RS-232/ IR / WebGUI
Baud Rate:	115200 bps
Power Consumption:	Max 12.5 W / Min 4 W
Power Supply:	External 5V 4A
Housing:	Metal Enclosure
Color:	Black
ESD Protection:	Human body model - ±12 kV [air-gap discharge] & ±8 kV
Operating Temperature:	32 to 122 °F (0 to 50 °C) 10%~90%, non-condensing
Storage Temperature:	-40 to +158 °F (-40 to +70 °C)
Dimensions:	Device (including protrusions): 8.50" (216 mm) W x 5.00" (127 mm) D x 1.75" (45 mm) H Shipping: 11.1" (280 mm) W x 9.25" (235 mm) D x 3.23" (82 mm) H
Weight:	Device: 2.05 lbs. (0.93 kg) Shipping: 4.25 lbs. (1.92kg)
EMI/EMC:	CE, FCC Class B
MTBF:	90,000 hours
Warranty:	3-years

